



DURAFOB UHF



FUNCTIONALITY

RF Protocol:	ISO/IEC 18000-6C
Operating Frequency:	UHF - 860-960 MHz
Memory Configuration:	96-EPC Bits, 512 User Bits, 64 Bit Unique TID 32 Bit Access and Kill Passwords
R/W Capability:	Read/Write

PERFORMANCE

Read Range:	UP to 1"
Quality Guarantee:	100%
Orientation:	Two Face Read
IP Rating:	IP68

PHYSICAL

Material:	Plastic
Mounting System:	Key Ring
Color:	Yellow, Black, White, Blue, Grey

OPERATIONAL

Max Temperature Exposure:	260°F/ 125°C
Min Temperature Exposure:	-40°F/ -40°C
Continuous Max Service Temperature:	260°F/ 125°C
Continuous Min Service Temperature:	-40°F/ -40°C
Water and Ice Proof:	Yes

DIMENSIONS

Weight:	7g / .25 oz
Dimensions:	1.65" x 1.4"
Thickness:	.024"



RECOMMENDED TAG APPLICATIONS

- Safety:** Fall Protection
- Access Control:** Security Fob

Visit www.infochip.com to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email sales@infochip.com or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

Where is it?

What is it?

Is it safe to use?

(877) 747-2447

sales@infochip.com

www.infochip.com