



# TACK TAG



## FUNCTIONALITY

<b>RF Protocol:</b>	EPC Class 1 Gen 2; ISO 18000-6C
<b>Operating Frequency:</b>	UHF - 860 to 960 MHz
<b>Memory Configuration:</b>	96-Bit EPC; 512 User Bit Memory; 64-Bit TD
<b>R/W Capability:</b>	Read/Write

## PERFORMANCE

<b>Read Range:</b>	Up to 3ft. (results may vary)
<b>Quality Guarantee:</b>	100%
<b>Orientation:</b>	Readable in 360° - Orientation May Degrade Performance
<b>IP Rating:</b>	IP68

## PHYSICAL

<b>Material:</b>	Stainless Steel
<b>Mounting System:</b>	Adhesive, Welding
<b>Color:</b>	Stainless Steel

## OPERATIONAL

<b>Max Temperature Exposure:</b>	300°F/ 150°C
<b>Min Temperature Exposure:</b>	-40°F/ -40°C
<b>Continuous Max Service Temperature:</b>	300°F/ 150°C
<b>Continuous Min Service Temperature:</b>	-40°F/ -40°C
<b>Water and Ice Proof:</b>	Yes

## DIMENSIONS

<b>Weight:</b>	9.2g / 0.32 oz
<b>Dimensions:</b>	Diameter .75"
<b>Thickness:</b>	.19"



## RECOMMENDED TAG APPLICATIONS

**Oil & Gas:** Industrial Equipment, Tools & Machinery

Visit [www.infochip.com](http://www.infochip.com) to view our demo videos and learn more about the InfoChip suite of tags, readers and asset management software. For pricing and details, please email [sales@infochip.com](mailto:sales@infochip.com) or call Toll Free 1-844-414-8247 in the US or 1-877-747-2447 in Canada or the US.

**Where is it?**

(877) 747-2447

**What is it?**

[sales@infochip.com](mailto:sales@infochip.com)

**Is it safe to use?**

[www.infochip.com](http://www.infochip.com)