

**ZONE 1/21  
CL I / DIV 1**



## IS530.1

**Always a step ahead!  
The smart and innovative  
Zone 1/CI I Div1-smartphone  
with the most advanced  
technology:**

**First Bluetooth® 5 industrial  
smartphone with multifunc-  
tional ISM interface, a huge  
internal memory 64 GB and  
the highest camera resolution  
of its class.**

➤ Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ➤ i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ➤ © 2020 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1029MD01REV07\_EN\_08.2020

## TECHNICAL FEATURES



ATEX approval:  
EX-Zone 1/21  
⊙ II 2G Ex ib IIC T4 Gb  
⊙ II 2D Ex ib IIC T135°C Db IP6X



IECEx approval:  
EX-Zone 1/21  
Ex ib IIC T4 Gb  
Ex ib IIC T135°C Db IP6X



Approved for  
North America:  
Class I, II, III Division 1  
Groups A B C D E F G, T4  
Intrinsically Safe



Android™ 9



2,4GHz + 5GHz: IEEE  
802.11a/ b/g/n/ac/e/k/r/h  
with max. 8 connections  
hotspot



GSM 850/900/1800/  
1900 MHz  
WCDMA: UMTS B1/2/4/5/8  
LTE-FDD: B1/2/3/4/5/7/8/12  
with MFBI B13/14/17/20/25/  
26/28A/28B/29/30/66  
LTE-TDD: B38/B39/B40/B41  
TD-SCDMA: B34/B39



Bluetooth® 5



Size: 155 x 80 x 25 mm,  
weight: 325 g



External memory  
microSD up to 128 GB



2 cameras: 13 MP AF  
rear camera and 5 MP  
front camera



Qualcomm Snapdragon  
SDM660 Octa-Core  
Kryo Gold-Quad cores  
2.2GHz  
Kryo Silver-Quad cores  
1.8GHz  
4 GB RAM  
64 GB internal memory  
54 GB accessible



Dual micro SIM



Near Field  
Communication



SOS-key  
Loneworker protection  
LWP ready (third party  
application required,  
based on country  
specific regulations)



Universal, lateral  
ISM interface

## FURTHER FEATURES



Waterproof: 1 hour  
up to 2 m, impervious to  
dust and microparticles



Operation range from  
-20 °C to 60 °C



Drop-protection,  
tested against: vibrations,  
shock and extreme  
temperatures.



4,5" Gorilla Glass®  
3. generation,  
resolution 854 x 480 pixel



Usable with gloves



Amplified loudspeaker



3600 mAh battery,  
replaceable,  
3,8V; 13,68Wh



GPS, A-GPS, Glonass,  
Beidou, Galileo



Gyroscope, acceleration,  
magnetic- and proximity  
sensor



Magnetic charging port

## CONTENTS

Smartphone, battery, i.safe PROTECTOR 2.0 USB cable, i.safe PROTECTOR 3.0 USB cable, charger, screwdriver, quick start manual and safety instructions